

Data Sheet

HØRNING Mastic E850 Filler



HØRNING Mastic E850 Filler is used for indoor and outdoor repairs without finishing, as well as full parting of floors.

HØRNING Mastic E850 Filler is water-based and ready for use.

HØRNING Mastic E850 Filler – Data Sheet

Product

- *Water-based filler - ready for use.
- *Made from various dry matter (>80%), water app. 20%.

Physical specification

- *Color: 4 standard colours.
- *PH value: 7 - 8.
- *Density: About 1.68 kg/l.
- *Working temperature: Between 5°C and 30°C.

Use

- *Used for both indoor and outdoor repairs without finishing.
- *Ready to use for full parting of unfinished wood floors, e.g. industrial parquet.
- *Store in closed bucket
- *Clean tools with water.

Note

- *Using HØRNING Mastic does not require protective clothing or venting.
- *HØRNING Mastic filler sinks and cracks not during drying.
- *Can be finished - even with stain.
- *Short drying time.
- *Minimal dust when grinding.
- *Very resistant to moisture.

Packaging

- *7 kg plastic bucket.

Storage

- *Store cold but frost-free.
- *Can be stored up to 1 year. Recommended room temperature between 5°C and 30°C.

Environment

- *HØRNING Mastic E850 has been tested and approved according to Eurofins IAC Gold criteria.

