

Data Sheet

Versailles panel



HØRNING Versailles panels are a craft based unique flooring solution for architecture that demands special solutions.

The Versailles pattern consists of beautiful, symmetrical design elements, providing a completely unique expression. The patterns can be combined with borders, adding an extra aesthetic dimension.

HØRNING Versailles patterns are available in oak in different grades.

If you have any questions, feel free to contact us – we are ready to assist.

Versailles Panel – Data Sheet

HØRNING Versailles Panel can be crafted in either solid or engineered timber flooring.

Dimension and Construction (Standard)

Solid

Thickness: 16 / 21 mm
Width / length: 790 x 790 / 932 x 932 mm

Grading: Exquisite, Living, Country

Additional: Beveling, brushing and beveling, or hand finished look.

Type of wood: Oak
Other wood species are available upon request.

Engineered

Thickness: 15 / 20 mm
Width / length: 800 x 800 / 980 x 980 mm

Wear layer: 3,8 / 5,5 mm

Grading: Exquisite, Living

Profile: Bevels - Square edges inside the panel, micro bevels on outer edges

Type of wood: Oak
Other wood species are available upon request.

Moisture content in the wood: 8% (+/- 2%)

Surface

Delivered as standard untreated, filled, and sanded. Inquire about lacquering, oiling, hardwax oiling, brushing, or smoking. Treated planks always have a bevel on all 4 sides.

Grades

Grades vary from wood specie and dimension. Wood is a natural material, thus there will always be variations compared to descriptions and photos. Samples will only show dimension and construction and not the grade. It is certain that variations will exist between small samples and the actual deliveries.

Exquisite

General uniform colour and wood structure. Variations due to growth conditions will exist. In principle free of knots and sapwood. Whirls, small scratches, cross grains and brown heart may be found to a small extent.

Living

A more characteristic look with natural colours and wood structure. In principle free of open knots, cracks, pith etc. Whirls, healthy knots, small scratches, cross grains and silicon stains may be found. Sapwood or brownheart will be found depending of the wood specie.

Country

A very characteristic look with all natural colour variations and structures. Knots, sapwood and brownheart is found. Very small open knots and scratches may be found. '

Under-floor heating

Under-floor heating may be used. Please see the installation guide.

Indoor climate

It is important that the surface temperature never exceeds 27 degrees.

The relative humidity in the air (R.H.) must always be between 35-65% before, during and after installation.

Always study the installation guide from HØRNING prior to installation.

Fire class

Dfl-s1
Ask for our Declaration of Performance (DOP).

Environment

FSC and/or PEFC available upon request.

HØRNING is Eurofins Indoor Air Comfort Gold certified and offers a wide range of certified products.

With EPD, HØRNING can document the carbon footprint of selected products.

CE Marking

HØRNING floors are CE-certified in accordance with the EU declaration for indoor-use wood floors; EN 14342.